

SATELLITES TRACKING

Channels	1408
BDS	B1I, B2I, B3I, B1C, B2a, B2b
GPS	L1C/A, L1C, L2C, L2P(Y), L5
GLONASS	G1, G2, G3
Galileo	E1, E5a, E5b, E6
QZSS	L1C/A, L1C, L2C, L5
NavIC	L5
SBAS	WAAS, EGNOS, SDCM, BDSBAS, GAGAN
L-Band	Upgradable
Cold start	<30s
RTK Initialization Time	<5s(typical)
RTK initialization reliability	>99.9%
Re-acquisition	<1s

ACCURACY

Standalone	1.5m Horizontally 2.5m Vertically
DGPS	0.4m Horizontally 0.8m Vertically
Static post-processing	2.5mm+0.5ppm Horizontally 5mm+0.5ppm Vertically
RTK	8mm+1ppm Horizontally 15mm+1ppm Vertically
PPP*	5cm Horizontally 10cm Vertically
SBAS	< 1.0 m 3D RMS
Time Accuracy	20ns

TILT FUNCTION (PLUS MODEL ONLY)

Tilt range	60° tilt range
Tilt survey accuracy	±2.5cm within 60° tilt range
IMU Initialization time	5s

COMMUNICATION

Bluetooth	BT4.2 BR/EDR
WiFi	802.11 b/g/n
4G	LTE-FDD: B1/B3/B5/B7/B8/B20/B28 LTE-TDD: B38/B40/B41 GSM: Band 850/900/1800/1900 MHz

ELECTRICAL

Battery	4000mAh
Input Voltage	5V, 2A

PHYSICAL

Size	135*70*22mm (L*W*H)
Weight	199 g

FUNCTIONALITY

Visual Alert	Two bright lights flash to provide a warning signal
Auditory Alert	Emits a loud and distinctive sound as an alert
vibration alert	The wearable vibrates vigorously to alert the wearer.
UWB	Reserved

ENVIRONMENTAL

Waterproof & dustproof	IP67
Shock	Designed to survive a 1.5 m drop onto concrete
Operating temperature	-20 °C to + 60 °C
Storage temperature	-20 °C to + 60 °C
Humidity	100% non-condensing

APPLICATION

- Land Surveying
- Construction Safety
- Geographical information collection
- Personnel positioning
- Vehicle trajectory tracking
- Inspection and investigation
- Other high precision applications

All specifications are subject to change without notice.

©2024 SingularXYZ Intelligent Technology Ltd. All rights reserved. SingularXYZ® is the official trademark of SingularXYZ Intelligent Technology Ltd., registered in People's Republic of China, EU. All other trademarks are the property of their respective owners.

P2

GNSS SAFETY SOLUTION

Smart Alerts, Safer Work – Your Safety Guardian



P2 GNSS SAFETY SOLUTION

In a wide range of applications such as construction, railway, and inspection, ensuring the safety of personnel is paramount. SingularXYZ has integrated high-precision GNSS technology into this critical area, introducing the effective P2 GNSS Safety Solution.

This solution guarantees a more secure working environment through centimeter-level positioning, alert functions and a geo-fence platform. Additionally, it offers extensive customization options for tailored needs.





Wearable Design



Centimeter-Level Positioning


4G
Transmission

10Hrs
Battery Life


IP67
Protection

Triple Safety Alerts
Voice, Vibration, Light

APPLICATIONS



CUSTOMIZED CLOUD MANAGEMENT PLATFORM



- Comprehensive Device Management
- Remote Upgrade & Configuration
- Real-time Status & Position Monitoring
- Highly Customizable Solutions

Customized Functions of SingularThings



FIELD TERMINAL CONFIGURATION SOFTWARE



- Bluetooth Connection
- Work Mode Configuration
- Device Status Checking
- Firmware Upgrade